## SUBSTITUTE FOR SENATE BILL NO. 337

A bill to amend 1970 PA 132, entitled

"An act to provide for the filing of surveys in the office of the register of deeds relative to land divisions; and to prescribe the conditions of the survey,"

by amending sections 1, 2, and 3 (MCL 54.211, 54.212, and 54.213), sections 1 and 3 as amended by 2018 PA 193 and section 2 as amended by 1988 PA 24.

## THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

- 1 Sec. 1. (1) If <del>lands are surveyed into parcels a survey is</del>
  - made to describe a parcel for the division of a parcel or tract
- 3 under sections 108 to 109b of the land division act, 1967 PA 288,
- 4 MCL 560.108 to 560.109b, or any boundary survey where permanent
- 5 corners are monumented, the professional land surveyor who prepared





- 1 the survey the grantor or lessee shall, at or before the time the
- 2 property is conveyed or leased, record a certified copy in the
- 3 office of the register of deeds in the county in which the land is
- 4 situated.located a certified true copy of the original survey map
- 5 that complies with section 3, unless the professional surveyor who
- 6 prepared the survey has already done so.
- 7 (2) If a survey is made for the purposes of describing to
- 8 describe a parcel in a conveyance of title or describing a parcel
- 9 as created in a lease for a term of 1 year or more, a certified
- 10 copy of that survey shall, within 90 days after the delivery of the
- 11 survey to the professional land surveyor's client, be filed for
- 12 recording with longer, the grantor or lessor, at or before the time
- 13 the property is conveyed or leased, shall record with the register
- 14 of deeds in the county in which the land is situated. located a
- 15 certified true copy of the original survey map that complies with
- 16 section 3, unless the professional surveyor who prepared the survey
- 17 has already done so.
- 18 (3) The requirements of this act are in addition to those of
- 19 the land division act, 1967 PA 288, MCL 560.101 to 560.293. Land
- 20 platted under that act, land surveyed under section 66 of the
- 21 condominium act, 1978 PA 59, MCL 559.166, or land previously
- 22 surveyed and recorded and for which no change in boundary
- 23 description is made from a previously recorded survey, need not be
- 24 recorded under this act.
- 25 Sec. 2. (1) The survey shall be performed and the A certified
- 26 survey map shall meet the requirements of this section and section
- 27 3. A certified survey map must be prepared only by a land
- 28 professional surveyor licensed in this state.
- 29 (2) All corners—Except as provided in subsection (3), each

- corner of the survey shall be meet all of the following
  requirements:
- (a) Be monumented in the field with a permanent markers which
   possess marker that possesses a magnetic field unless previously
   monumented with iron stakes. reapped
- 6 (b) Be capped with some a device legibly showing the last 5
  7 digits of the license number of the licensed land professional
  8 surveyor placing them, and shall include points the monument.
  - (c) Include both of the following:
- 10 (i) Points of intersection of boundary or lot lines with
  11 highways, streets, alleys, section lines, and meander lines. , and
  12 corners
- (ii) Corners of the United States public land survey Public
   Land Survey from which the parcel or parcels are described.
- 15 (3) If a monument cannot conveniently be set because of a
  16 physical obstruction such as pavement, a large rock, a large root,
  17 or a utility cable, the following apply:
- 18 (a) Subject to subdivision (b), the professional surveyor 19 shall do both of the following:
- 20 (i) Establish an alternative monument that is permanent and 21 identifiable, such as a drill hole or an "X" chiseled in concrete.
- 22 (ii) Reference the corner by bearing and distance from 2 23 different monumented corners of the survey.
  - (b) If compliance with subdivision (a) is not feasible, the professional surveyor shall monument the corner in any practical manner and show its relationship on the certified survey map.
- Sec. 3. (1) The **certified** survey map under <del>section 1 shall be</del>

  prepared on durable white paper 8-1/2 inches wide by 14 inches

  long. Lines on a map shall be made with nonfading black ink on a

9

24

25

- 1 scale of not more than 500 feet to an inch. The scale shall be
- 2 shown on the map, and a true scale reproduction of the map pursuant
- 3 to the records reproduction act, 1992 PA 116, MCL 24.401 to 24.406,
- 4 shall be recorded. The map shall sections 1 and 2 must meet all of
- 5 the following requirements:
- 6 (a) Include a certificate signed and sealed by the licensed
- 7 Bear the seal and signature of the professional surveyor who
- 8 surveyed the parcel or parcels. The certificate shall meet all of
- 9 the following requirements:
- 10 (b)  $\frac{(i)}{(i)}$  Be prepared on durable white paper 8-1/2 inches wide
- 11 and 14 inches long.
- 12 (c) Be prepared by computer aided drafting (CAD), typed,
- 13 lettered, or otherwise reproduced legibly with nonfading ink
- 14 pursuant to the records reproduction act, 1992 PA 116, MCL 24.401
- 15 to 24.406.
- 16 (d) Have lines at a scale indicated in writing numerically and
- 17 by graphic bar scale, and have text of a size readily legible for
- 18 the line scale selected.
- (e)  $\frac{(ii)}{(ii)}$  Give a clear, concise description of the land surveyed
- 20 by bearings and distances, commencing with a corner position marked
- 21 and established in the United States Public Land Survey, or
- 22 reestablished in accordance with by accepted methods.
- 23 (iii) Include the relative positional precision of each corner,
- 24 which shall be within limits accepted by the practice of
- 25 professional surveying.
- 26 (iv) Include certification by the licensed professional
- 27 surveyor that the requirements of this section have been met.
- **28 (f)** For land not included in a platted subdivision or
- 29 condominium, include the exterior boundaries of the land surveyed

- 1 and divided, together with the line or lines leading to the United
- 2 States Public Land Survey corner, or corners, from which the land
- 3 is described. A
- 4 (g) Define a boundary along a lake or stream shall be defined
- 5 by a meander an intermediate traverse line connecting the side
- 6 boundaries of the parcel.
- 7 (h) If a lot in a recorded platted subdivision is surveyed or
- 8 divided, reference the exterior boundaries of the lot surveyed and
- 9 divided shall be referenced to existing lot corners and the
- 10 controlling monuments used for that survey.
- (i) (c) If the boundary of the parcel follows or parallels a
- 12 section line, all of the following requirements:
  - (i) One of the following requirements:
- 14 (A) The section line shall be defined at its extremities by
- 15 corners established in the United States Public Land Survey, or by
- 16 corners reestablished pursuant to by accepted methods, or by
- 17 protracted quarter section corners, whether or not the protracted
- 18 quarter section corners are monumented under the state survey and
- 19 remonumentation act, 1990 PA 345, MCL 54.261 to 54.279.
- 20 (B) Other protracted division lines shown in the United States
- 21 Public Land Survey shall be defined at their extremities by corners
- 22 established pursuant to accepted survey methods.
- 23 (ii) Each corner of the United States Public Land Survey shall
- 24 be duly witnessed under the corner recordation act, 1970 PA 74, MCL
- **25** 54.201 to 54.210d.
- 26 (iii) The certified survey map shall indicate the kind of
- 27 object, the bearings and distances to the object, and the kind of
- 28 monument and material of monumentation the monument marking the
- 29 corner.

- 3 (i) If the curve is contained within the line, by the points of
  4 curvature and tangency and compound curvature, central angle,
  5 length of arcs, radius, and length and bearing of the long chord.
- 6 (ii) If the curve is only partially contained within the line,
  7 by the length of arc along the curve, radius, and length and
  8 bearing of the short chord.
- $\mathbf{9}$  (iii) If the curve is not regular, by traverse courses and  $\mathbf{10}$  distances.
- 11 (k) (e)—If an exterior boundary line shows a bearing or length
  12 that varies from that recorded in an abutting plat, condominium, or
  13 certified survey map, include the following note shall be placed
  14 along the line: "previously recorded as (show bearing or length or
  15 both)".
- 16 (l) (f) Include all of the following:
- 17 (i) The length and bearing of each line.
- 18 (ii) The exact width of the right-of-way of each street,19 highway, alley, and easement.
  - (iii) The distance on a boundary or lot line from the point of intersection with a meander an intermediate traverse line to the apparent ordinary high-water line of Great Lakes waters and to the water's edge of any inland lakes and streams.lake or stream and the date of the survey to the water's edge.
- 25 (iv) A north arrow properly oriented.
- 26 (v) A certification by the professional surveyor that the map 27 meets the requirements of this subsection.
- (2) The register of deeds shall accept certified survey mapsprepared pursuant to this section upon payment of the regular fee

2021

22

23

- 1 as provided in section 2567(1)(a) of the revised judicature act of
- 2 1961, 1961 PA 236, MCL 600.2567. The register of deeds shall
- 3 consecutively number the maps and record them in bound volumes or
- 4 in a manner adapted to a system of preserving records pursuant to
- 5 the records reproduction act, 1992 PA 116, MCL 24.401 to 24.406.
- 6 The maps shall be known as the "certified survey maps of
- 7 ..... county", and shall become be kept as a part of the
- 8 land records of the county. The register of deeds shall keep a
- 9 separate card file or electronic file of the county land records
- 10 system. The file shall be indexed within the land records system.
- 11 The file shall specify the unique identifying number or liber and
- 12 page of the recorded surveys in the bound volume or other record.
- 13 The specification shall be by the section, township, and range and,
- 14 if the map is a resurvey within the a recorded plat, by the title
- 15 of the <del>recorded</del> plat.